This listing of the claims will replace all prior versions and listings of the claims in the application.

## **Listing of the Claims:**

1. (Currently Amended) A washing apparatus comprising:

a body having a first work surface surrounded by an upstanding wall structure which confines fluid from flowing off the first work surface, and having a drain opening in the first work surface;

a coupling suitable to link the drain opening to a building waste disposal system; and

a platform removably positioned on the first work surface and unfastened to the body, the platform having a second work surface that is raised upward from the first work surface, wherein fluid flowing off side edges of the second work surface flows onto the first work surface.

- 2. (Original) The washing apparatus as recited in claim 1 wherein the first work surface is concave.
- 3. (Original) The washing apparatus as recited in claim 1 wherein the first work surface has an elliptical perimeter.
- 4. (Original) The washing apparatus as recited in claim 3 wherein the second work surface has an elliptical perimeter.

Claims 5-6 (Withdrawn).

- 7. (Original) The washing apparatus as recited in claim 1 wherein the platform further comprises a plurality of supports which raise the second work surface from the first work surface.
- 8. (Original) The washing apparatus as recited in claim 1 wherein the platform further comprises a plurality of legs which raise the second work surface from the first work surface.
- 9. (Original) The washing apparatus as recited in claim 1 wherein the second work surface is convex thereby directing water onto the first work surface.
- 10. (Original) The washing apparatus as recited in claim 1 further comprising a spout which emits a stream of water onto the first work surface.
- 11. (Original) The washing apparatus as recited in claim 10 wherein the spout emits a laminar stream of water onto the first work surface.
- 12. (Original) The washing apparatus as recited in claim 1 further comprising a bowl removably positionable on one of the first work surface and the second work surface, the bowl having a bottom portion with an aperture there through and an exterior lower surface having a sealing means which extends around the aperture to engage the respective one of the first work surface and the second work surface to inhibit flow of fluid outward from the bowl.

- 13. (Original) The washing apparatus as recited in claim 12 wherein the sealing means comprises a gasket attached to the exterior lower surface of the bowl.
- 14. (Currently Amended) A plumbing fixture for washing objects comprising:
  a body having a first work surface surrounded by a structure that prevents a fluid
  from flowing outward from the first work surface and off the plumbing fixture; and having
  a drain opening to receive the fluid flowing from the first work surface;

a coupling suitable to link the drain opening to a building waste disposal system; and a platform removably positioned on the first work surface and unfastened to the body, the platform having a second work surface that is convex and raised upward from the first work surface, wherein fluid flowing from the second work surface flows into the drain opening of the body.

- 15. (Original) The plumbing fixture as recited in claim 14 wherein the first work surface has an elliptical perimeter.
- 16. (Original) The plumbing fixture as recited in claim 15 wherein the second work surface has an elliptical perimeter.
- 17. (Original) The plumbing fixture as recited in claim 15 wherein the platform further comprises a plurality of legs which raise the second work surface from the first work surface.

Cancel Claim 18.

Claims 19-24 (Withdrawn).